



DISC LED Slimline Pendant™

The Indirect DISC LED Slimline Pendant mount is perfect for lighting Indoor Sports Facilities. Energy Efficient Indirect LED lighting is aesthetically pleasing to players and spectators. Visibility is improved by eliminating glare and having an evenly lit facility. Return on Investment is 30% ROI + when replacing 1000 Watt HID's.



With indirect lighting safety is increases as glare from direct lighting causes accidents. Most athletes prefer the superior aspects of indirect lighting.

TECHNICAL INFORMATION

Part No. DISC LED
Specify: (Wattage, Voltage & Mounting)
Input Voltage: 120-277 or 347-480
CCT: 5100
CRI: Ra85
Dimmable: PWM 0-10V
Weight: 30 lbs.
LED Chip: NICHIA
DRIVER INVENTRONICS: Remote Driver available.
NTC: Thermal Sensing and Protection for LED Module

Constant Natural Positive Air Flow Keeps LEDs and Driver COOL Without Fans

Housing and Heat sink: Pure Aluminum
Lens: Clear Safety Glass (CGL), Clear Polycarbonate Lens (CPL) or Frosted (FPC)
Working Temperature: -30 to 45C
Power Factor: 99.9
Rated for: Damp Locations - NO Fans.
Warranty: 10 year
Accessories: Wireless Bluetooth Network Controls: Occupancy Motion Sensors, Dimming, High-end Trim and Scheduling.
Lumen Output: See below.



		VOLTS			
		120	277	347	480
INDIRECT - 73,471 LUMEN	WATTS	481	473	479	478
	AMPS	4.01	1.8	1.39	1.05
INDIRECT - 81303 LUMEN	WATTS	565	552	561	560
	AMPS	4.71	2.08	1.61	1.16
INDIRECT - FPC 62,000 LUMEN	WATTS	481	473	479	478
	AMPS	4.01	1.8	1.39	1.05

EXAMPLE:	DISC-LED	IP INDIRECT PENDANT	81,303	120-277V	DIM	OS	LENS
SECTIONS:	SERIES	MOUNTING OPTION	NOMINAL LIGHT	INPUT VOLTAGE WIRELESS	0-10V	SENSORS	
OPTIONS:	DISC-LED	IP	73,471 LUMENS	120-277V 50/60HZ	DIM-PWM 0-10V	OS	CGL
			81,303 LUMENS	347-480V 50/60HZ	HT-HIGHEND TRIM	HT	CPL
			62,000 LUMENS	277-480V	DAYLIGHT HARVESTING	DH	FPC

BEST Lights are made in Michigan

